

CAMC65BK

SPECIFICATIONS

<i>Conductors</i>	<i>Material</i>	Stranded oxygen-free copper
	<i>Size</i>	28 * 0.10mm (0.22mm ²)
<i>Insulation</i>	<i>Material</i>	PE
	<i>Colour</i>	cdhcbU
	<i>Shorehardness (A)</i>	52 +/-3
<i>Screen</i>	<i>Spiral Screen</i>	Stranded oxygen-free copper
	<i>Coverage</i>	Approx. 90% density
	<i>Size</i>	0.10mm, AWG 24
<i>Outer Jacket</i>	<i>Material</i>	PVC/NBR
	<i>Colour</i>	cdhcbU
	<i>Overall Diameter</i>	*(mm +/-0.2\$mm
	<i>Shorehardness (A)</i>	60 +/-3
<i>Technical Data</i>	<i>Test Voltage</i>	C/C: > 1kV
		C/S: > 0.5kV
		at 50Hz, effective for 1 minute
	<i>Insulation Resistance Min:</i>	20M Ohm/Km at 20°C
	<i>Conductor Resistance Max:</i>	86 Ohm/Km at 20°C
	<i>Temperature Rating</i>	Static: -30°C to +70°C
		Operating: -20°C to +70°C
	<i>Capacitance</i>	C/C: 50pF/m @ 1kHz
		C/S: 110pF/m @ 1kHz
	<i>Operating Voltage</i>	Max: 50/75V AC/DC
	RoHS Compliant	